



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : TANEX CEMENT-EX 10 L  
Identification number : 61165

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Cleaning agent  
Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

Company : Tana Chemie GmbH  
Rheinallee 96  
55120 Mainz  
Telephone : +49613196403  
Telefax : +4961319642414  
E-mail address : Produktsicherheit@werner-mertz.com  
Responsible/issuing person  
Contact person : Product development / product safety

#### 1.4 Emergency telephone number

112  
Centru za kontrolu otrovanja u Zagrebu na tel. (01) 2348 342  
+49(0)6131-19240

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin irritation, Category 2 H315: Causes skin irritation.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.  
H319 Causes serious eye irritation.

Precautionary statements : P102 Keep out of reach of children.

##### Prevention:



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

P264 Wash hands thoroughly after handling.  
P280 Wear protective gloves/ eye protection/ face protection.

**Response:**  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

Safety data sheet available on request.

### 2.3 Other hazards

No information available.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Cleansing agents, acidic.

#### Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification	Concentration (% w/w)
sulphamidic acid	5329-14-6 226-218-8 01-2119846728-23	Eye Irrit. 2; H319 Skin Irrit. 2; H315 Aquatic Chronic 3; H412	>= 10 - < 15

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.

If inhaled : Move to fresh air.  
Consult a physician after significant exposure.

In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.

In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

Protect unharmed eye.  
Continue rinsing eyes during transport to hospital.

If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : corrosive effects  
Irritation

Risks : No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : For specialist advice physicians should contact the Poisons Information Service.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.  
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Neutralize with chalk, alkali solution or ammonia.  
Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

### 6.4 Reference to other sections

For personal protection see section 8., Treat recovered material as described in the section "Disposal considerations"., Refer to section 15 for specific national regulation.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. To avoid spills during handling keep bottle on a metal tray.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store at room temperature in the original container.

Other data : No decomposition if stored and applied as directed. Protect from frost.

### 7.3 Specific end use(s)

Specific use(s) : Cleaning agent

---

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

DNEL



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

**sulphamidic acid**  
**5329-14-6:**

- : End Use: Consumers  
Exposure routes: Ingestion  
Value: 1,06 mg/kg
  
- End Use: Workers  
Exposure routes: Inhalation  
Value: 7,5 mg/m3
  
- End Use: Consumers  
Exposure routes: Inhalation  
Value: 1,85 mg/m3
  
- End Use: Consumers  
Exposure routes: Ingestion  
Potential health effects: Long-term systemic effects  
Value: 5 mg/kg
  
- End Use: Workers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 10 mg/kg
  
- End Use: Consumers  
Exposure routes: Skin contact  
Potential health effects: Long-term systemic effects  
Value: 5 mg/kg

**PNEC**

**sulphamidic acid**  
**5329-14-6:**

- : Fresh water  
Value: 0,3 mg/l
  
- Marine water  
Value: 0,03 mg/l
  
- intermittent release  
Value: 0,3 mg/l
  
- STP  
Value: 200 mg/l
  
- Fresh water sediment  
Value: 0,3 mg/kg
  
- Marine sediment  
Value: 0,3 mg/kg
  
- Soil  
Value: 3 mg/kg
  
- Fresh water  
Value: 0,048 mg/l
  
- Marine water  
Value: 0,0048 mg/l
  
- STP  
Value: 2 mg/l
  
- Fresh water sediment



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

Value: 0,173 mg/kg

Marine sediment  
Value: 0,0173 mg/kg

Soil  
Value: 0,00638 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye protection : If splashes are likely to occur, wear:  
Tightly fitting safety goggles

#### Hand protection

Material : For prolonged or repeated contact use protective gloves.  
It is suggested the usage of chemical resistant gloves made of butyl rubber or nitrile rubber category III according to EN 374-1: 2003 (0,4 mm).  
As alternative, a different type of gloves might be used if, accordingly to the recommendations of the producer, guarantee the same level of protection.

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.  
not required under normal use

Respiratory protection : Not required; except in case of aerosol formation.  
Recommended Filter type:  
ABEK-P3-filter

#### Environmental exposure controls

General advice : Do not flush into surface water or sanitary sewer system.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : Aqueous solution

Colour : pink

Odour : characteristic

Odour Threshold : No data available

pH : ca. 0,4

Melting point/range : No data available

Boiling point/boiling range : No information available.



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Flammability (liquids)	: Not classified as supporting combustion according to the transport regulations.
Burning rate	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: ca. 1,079 g/cm <sup>3</sup>
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
acid reserve	: 5,89 g/100g
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2 Other information

none

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions., No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under recommended storage conditions., No decomposition if used as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Protect from frost.



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

### 10.5 Incompatible materials

Materials to avoid : No data available

### 10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

Other information : No hazardous decomposition products are known.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Our company is strongly against animal testing.  
Our company does not place any orders for animal testing for the finished product or the ingredients.  
However, as a result of EU legislation (REACH Regulation), the manufacturers of ingredients or EU importers are obliged to test ingredients with regard to their effects on human health and the environment before they are brought onto the market. Some of the tests made necessary by this took place decades ago.

#### Product

Skin corrosion/irritation : Extremely corrosive and destructive to tissue.

Serious eye damage/eye irritation : May cause irreversible eye damage.  
Causes serious eye irritation.

Respiratory or skin sensitisation : No data available

Germ cell mutagenicity : Not Rated

Carcinogenicity : Not Rated

Reproductive toxicity : Not Rated

STOT - single exposure : The substance or mixture is not classified as specific target organ toxicant, single exposure.

STOT - repeated exposure : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration toxicity : Not Rated

Further information : No data available

#### **Components:** **sulphamidic acid** **5329-14-6:**

Acute oral toxicity : LD50 Rat: 3.160 mg/kg

LD50 Oral Rat: > 2.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes





## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

Acute dermal toxicity	: LD50 Rat: > 2.000 mg/kg Method: OECD Test Guideline 402 GLP: yes
Skin corrosion/irritation	: Species: Rabbit Result: Irritating to skin. Method: OECD Test Guideline 404
Serious eye damage/eye irritation	: Species: Rabbit Result: Eye irritation Method: OECD Test Guideline 405
Repeated dose toxicity	: Rat: 1000 mg/kg NOAEL: 1.000 mg/kg  Application Route: Oral Exposure time: 90 h Method: OECD Test Guideline 408

### SECTION 12: Ecological information

#### 12.1 Toxicity

**Components:**

**sulphamidic acid  
5329-14-6:**

Toxicity to fish	: LC50 (Pimephales promelas (fathead minnow)): 70,3 mg/l Exposure time: 96 h Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 71,9 mg/l Exposure time: 24 h Method: OECD Test Guideline 202
Toxicity to algae	: ErC50 : 48 mg/l Exposure time: 72 h Method: OECD Test Guideline 201

#### 12.2 Persistence and degradability

**Product:**

Biodegradability	: Remarks: The surfactant(s) contained in this preparation complies (comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents.
------------------	---

#### 12.3 Bioaccumulative potential

**Components:**

**sulphamidic acid  
5329-14-6:**

Bioaccumulation	: Remarks: No bioaccumulation is to be expected (log Pow <= 4).
Partition coefficient: n-	: log Pow: -4,34



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

octanol/water

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

Not relevant

### 12.6 Other adverse effects

**Product:**

Additional ecological information : There is no data available for this product.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
In accordance with local and national regulations.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

---

## SECTION 14: Transport information

### 14.1 UN number

**ADR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

### 14.2 Proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class

**ADR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

### 14.4 Packing group

**ADR**

Not dangerous goods

**IMDG**

Not dangerous goods

**IATA**

Not dangerous goods

### 14.5 Environmental hazards

**ADR**



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

Not dangerous goods

**IMDG**

Not regulated as a dangerous good

**IATA**

Not dangerous goods

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

For personal protection see section 8.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
TA Luft List (Germany) : Not applicable

: Total dust: Not applicable  
: Inorganic substances in powdered form: Not applicable  
: Inorganic substances in vapour or gaseous form: Not applicable  
: Organic Substances: : portionClass 1: < 0,01 %  
: Carcinogenic substances: : portionClass 2: < 0,01 %  
: Mutagenic: : < 0,01 %  
: Toxic to reproduction: Not applicable

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Update: Percent volatile: 1 %  
120,77 g/l  
VOC content excluding water

Volatile organic compounds (VOC) content : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Update: Percent volatile: 1 %  
10,8 g/l  
VOC content valid only for coating materials used on wood surfaces

according to Detergents Regulation EC 648/2004 : <5% Non-ionic surfactants, Perfumes

GISBAU (D) : GS 35

### 15.2 Chemical safety assessment

There is no data available for this product.



## TANEX CEMENT-EX 10 L

WM 0708722

Order number: 0708722

Version 4.2

Revision Date 05.02.2021

Print Date 09.03.2022

### SECTION 16: Other information

#### Full text of H-Statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

#### Further information

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Classification procedure:	H319	On basis of test data.
	H315	Calculation method

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.